

Office of the Dean (Academic)

Indian Institute of Engineering Science and Technology, Shibpur, Howrah-711 103

(Formerly Bengal Engineering and Science University, Shibpur)

Howrah- 711 103 , West Bengal, India

Notice Inviting Quotations

Corrigendum

for I-Card Printer (no: Dean/ac/01/2016-17 dt.20.05.16)

No. Dean/ac/01/2016-17

Date- 06.06.2016

Sealed quotations are invited for the supply of "card Printer (No Encoder) Color ribbon," as per the following technical specification. The relevant document can be downloaded from the website. Last date of submission of sealed quotation is 14.06.2016 by 3.00 p.m at the Office of the Dean Academic, IEST, Shibpur.

Amit Kumar Das

Prof. Amit Kumar Das 6/6/2016
(Dean ,Academic)



DEAN
(Academic)

Indian Institute of Engineering Science & Technology
Shibpur, Howrah-711103, West Bengal, India

Copy forwarded for information :-

1. Office of the Dean Academic Notice Board
2. Institute Website

PRINTER SPECIFICATION

Physical dimensions L 16.5 in. x W 7.8 in. x H 9.0 in. (41.25 cm x 19.5 cm x 22.5 cm) Weight 8 to 9 lbs (3.6 kg to 4.1 kg) depending on options Print resolution 300 dots per inch, 256 shades Electrical requirements 100/120V, 50/60 Hz 220/240V, 50/60 Hz Plastic cards accepted ISO ID-1/CR-80 size cards 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm) PVC with glossy laminate surface Clear cards Other core materials with PVC over laminates are optional.

Card thicknesses accepted 0.009 in. to 0.055 in. (0.2286 mm to 1.397 mm) Operating environment 60°F to 95°F (15°C to 35°C) 20% to 80% non-condensing humidity Storage environment 5°F to 140°F (-15°C to 60°C) 10% to 90% humidity Agency approvals FCC, CCC, RoHS, CE, UL, cUL

Standard features

Print capabilities One-sided edge-to-edge printing Continuous-tone, full-color, black-and white photos Alphanumeric text, logos and digitized signatures Variety of bar codes Background patterns Advanced Imaging Technology™ Print speed Full-color printing: Up to 160 cards per hour One-color printing: Up to 750 cards per hour Capacity Input hopper: Up to 100 cards, 0.03 in. (0.76mm) Output hopper: Up to 20 cards, 0.03 in. (0.76mm) Operating system support for printer driver: Microsoft® Windows 8 (32 bit) Windows 7 (32 bit) Windows XP (32 bit) Windows Server 2003 (32 bit) Printer driver User-adjustable image and color controls Stand-alone driver diagnostics Color image and test card preview Online user help Add text, image or pattern to topcoat Supply usage tab User-friendly operation Audible and visual message prompts Automatic card feed Operator-replaceable print head Continuous cleaning roller Easy-access components including quick-change ribbon cartridges Highly accessible card path Datacard® Certified Supplies featuring Intelligent Supplies Technology™ Automatic identification and validation for ribbons Automatic printer settings Low ribbon warning



Dr. Anurag Das
DEAN
(Academic) 6/6/2016
Indian Institute of Engineering Science & Technology
Shibpur, Howrah-711103, West Bengal, India